



Designed and manufactured in accordance with IALA recommendations, Sealite's range of Top Marks offer flexibility and reliability, and are a low cost and maintenance, high visibility solution to marine navigation.

The Top Marks are rotationally-moulded on-site from UV-stabilised virgin polyethylene with a wall thickness of 3mm, and are available in a range of IALA recommended colours and configurations to suit both IALA Regions A and B.

With a 26mm (1 inch) internal stainless-steel pole and industry standard 200mm OD mounting plate, Sealite's range of IALA Top Marks can be easily attached to any existing navigation aid.

Order Code	Description	Dimensions (mm) Height x Width •	Weight (kg/lbs) •
TM-PH.A	Port Hand Mark- 1 red cylinder (IALA Region A)	500 x 390	3.2 / 7
TM-PH.B	Port Hand Mark- 1 green cylinder (IALA Region B)	500 x 390	3.2 / 7
TM-SH.A	Starboard Hand Mark- 1 green cone (IALA Region A)	360 x 460	2.2 / 4¾
TM-SH.B	Starboard Hand Mark- 1 red cone (IALA Region B)	360 x 460	2.2 / 4¾
TM-CARD-N	North Cardinal Mark- 2 black cones	360 x 460	2.2 / 4¾
TM-CARD-S	South Cardinal Mark- 2 black cones	360 x 460	2.2 / 4¾
TM-CARD-W	West Cardinal Mark- 2 black cones	360 x 460	2.2 / 4¾
TM-CARD-E	East Cardinal Mark- 2 black cones	360 x 460	2.2 / 4¾
TM-ISO	Isolated Danger Mark- 2 black spheres	360 x 360	2.2 / 4¾
TM-SW	Safe Water Mark- 1 red sphere	360 x 360	2.2 / 4¾

• Specifications subject to change or variation without notice

**All Top Marks are manufactured with UV-stabilised virgin polyethylene, with a wall thickness of 3mm. Diameter of internal pole is 26mm.**



Head Office:  
Sealite Pty Ltd  
AUSTRALIA

Ph. +61 3 5977 6128  
Fax. +61 3 5977 6124  
Internet: www.sealite.com.au  
Email: info@sealite.com.au

USA Customers;  
Sealite USA  
USA (Gilford, NH)

Ph. (603) 524-6066  
Fax. (603) 524-8100  
Internet: www.sealiteusa.com  
Email: info@sealiteusa.com